



OSR

OIL STAIN REMOVER with the cleaning power of citrus



PRODUCT DATA

OSR is a powerful, citrus-based, liquid cleaner that absorbs petroleum-based stains and spills from concrete driveways, garage floors, patios, walkways and more. It outperforms conventional liquid degreasers and dry absorbent materials by removing both the spill and the stain. OSR turns from a liquid to a powder, allowing stains to literally be swept up or rinsed away without heavy scrubbing!

IMPORTANT: Read all directions thoroughly. Always wear gloves and eye protection.

DIRECTIONS: Read "LIMITATIONS" section before use. Remove loose dirt, debris and standing liquid from area. Shake OSR vigorously for 30 seconds, then pour directly onto stain, allowing it to spread out at least 1" beyond stain (liquid should not be applied more than 1/8" thick). Wait for OSR to dry to a powder, then sweep up or rinse away. If concrete appears dark, let area dry completely, then evaluate. If stain was not fully removed, repeat application. **Note:** Dry time depends on temperature, humidity and surface porosity; it can be shortened by increasing airflow. OSR is biodegradable and will not harm plants.

GARAGE OR SHOP FLOORS: When using OSR on smooth troweled garage floors, shop floors or carports – expect longer drying times due to poor ventilation and surface porosity. While scrubbing is not required, stubborn stains may be scrubbed with a shop broom after allowing 30 minutes for absorption. Then let OSR dry naturally or rinse with a hose or power washer.

LIMITATIONS: Do not use on asphalt or painted concrete surfaces. Do not use in wet or rainy conditions. OSR may cause discoloration on some surfaces – test on a small, inconspicuous area before applying to stain. OSR performs best in moderate humidity with temperatures above 70°F. Dry time will be longer in temperatures less than 60°F.

PRECAUTIONS: Flammable: Store in a cool, dry place. Never use near an open flame. For Eye Contact: Rinse eyes repeatedly with water and call physician. If Swallowed: Do not induce vomiting. Call physician immediately.

KEEP OUT OF REACH OF CHILDREN AND PETS.

ABSORBS AND LIFTS STAINS FROM CONCRETE WITHOUT SCRUBBING

Pour on, let dry and sweep (or rinse) away!



Safe to use:

- Non-caustic
- Phosphate free
- Biodegradable
- Water soluble
- Easy disposal

Also works on:

- Antifreeze
- Brake fluid
- Diesel fuel
- Grease
- Hydraulic fluid
- Transmission fluid
- Power steering fluid
- Tree sap



New 16 Oz.



Convenience products

306 Gandy Rd.
Auburndale, FL 33823 USA

How to treat concrete™

(800) 323-7357
e-mail: tech@seal-krete.com

PRODUCT NUMBER	UNIT SIZE	UPC CODE	CARTON QTY	CARTON CODE	CARTON SIZE (L X W X H)	CARTON SIZE (CUBIC FEET/LBS)	PALLET QTY. (CARTONS)
140001	1/2 gallon	0 15944 14001 9	6	9 00 15944 14001 2	13 1/8 X 10 3/4 X 10 1/4	.84 / 27	36
140016	16 ozs.	0 15944 14016 3	12	9 00 15944 14016 3	12 1/2 X 7 1/4 X 8 3/4	.46 / 13	80



OUTPERFORMS CONVENTIONAL DEGREASERS!