

SEAL KRETE®

WET-LOOK

CONCRETE/MASONRY SEALER

SEAL-KRETE® Wet-Look Sealer provides long-lasting surface protection, beauty and easy maintenance to a wide range of masonry and concrete surfaces. It protects against moisture damage while enhancing the natural colour of brick, slate, stone and similar surfaces. The acrylic polymer resin technology is environmentally friendly, has very low odour and is easy to use. The non-yellowing formula dries to a clear, semi-gloss to high-gloss finish depending on surface porosity and the amount of product applied.

Important: Read all directions thoroughly. Wear gloves and eye protection.

SURFACE PREP: Surface must be clean, dry and oil-free (remove oil stains with a degreaser or SEAL-KRETE OSR oil stain remover). Make sure all curing compounds and releasing agents have been removed. Repair cracks and surface breaks. Cover windows, doors, etc., before application and use caution when applying on windy days.

Note: Do not apply to concrete that has not cured for at least 30 days.

For new or smooth concrete, acid etching and neutralization are required for proper adhesion. Use a 1:3 solution of hydrochloric acid and water or SEAL-KRETE Clean-N-Etch and follow product directions. For complete procedure visit our web site.

APPLICATION: Read "LIMITATIONS" section before use. This sealer is ready-to-use; do not dilute. Stir but DO NOT SHAKE (shaking can create air bubbles which affect finish). Apply one coat with a garden sprayer or roller. Do not apply more than two coats. **Note:** Sealer appears milky white during application but dries to a clear finish.

Garden sprayer: lightly spray surface with a fan-tip spray pattern, then backroll to aid penetration and eliminate puddling. Remove overspray immediately with water.

Roller: dampen a short-nap (6mm - 10mm) roller with water, remove excess, then saturate with sealer. Roll onto surface keeping a wet edge to avoid streaks. Do not allow to puddle, foam or run.

COVERAGE: 4-8 m²/L (varies based on surface porosity). Second coat coverage is 50% greater.

DRY TIME: Dry to touch in 1 hour, recoat in 2 hours, allow foot traffic in 24 hours, vehicular traffic in 72 hours (25°C, 50% RH).

CLEAN-UP & STORAGE: Clean all tools immediately after use with soap and water. Store unused product in a dry place above 10°C. Do not use solvent-based cleaners on surface; clean occasionally with a mild soap and water solution.

LIMITATIONS: Do not apply to non-porous surfaces such as glazed tile or marble. Do not apply if rain is expected within 24 hours or if temperatures fall below 13°C within 24 hours of application. In rainy/icy conditions, surfaces can become slippery. To increase slip-resistance, add a non-skid additive (like SEAL-KRETE Clear Grip) to sealer before application.

CAUTION: KEEP OUT OF REACH OF CHILDREN.

FIRST AID: For Eye Contact: Flush with water for 15 minutes. For Skin Contact: Prolonged contact may cause irritation. Wash affected area with soap and water. If Swallowed: Induce vomiting and seek immediate medical attention. If Inhaled: If headache or nausea is experienced, remove the individual to fresh air. If symptoms persist, seek medical attention.

LIMITED WARRANTY: Manufacturer/seller makes no warranty of any kind except that this product is free from defect and is of merchantable quality. Buyer remedy for breach of warranty is limited to replacement of product or refund of purchase price.



- Clear
- Interior / Exterior
- Very Low Odour
- Water Based
- Acrylic Formula
- OTC-compliant
- For Use on Bare Surfaces:
 - Concrete
 - Brick Pavers
 - Cobblestone
 - Slate
 - Stone
 - Stamped Concrete

LIQUID PROPERTIES

Solids: 30%
 Proprietary Acrylic Resin
 Water Based
 Odor: Low
 Appearance: Milky White, Dries Clear
 VOC: Less than 100 grams per litre

COVERAGE GUIDELINES

	Material Coverage Approx. m ² /L
Brick	4
Smooth Concrete	7
Broom-finished Concrete	5
Stamped Concrete	5
Stone	7
Slate	6
Precast Pavers	4
Cobblestone	7
Exposed Aggregate	6
FLOOR-TEX ™ Textured Coating	7

Note: Actual coverage will vary depending on porosity of surface.



Provides a long-lasting "Wet Look" protective finish.

**IMPROVED – NOW URETHANE FORTIFIED
GREAT FOR PAVERS!**

