



HEAVY DUTY WATERPROOFER

FOR LOW DENSITY DECORATIVE CONCRETE AND MASONRY

PRODUCT DATA

IMPORTANT: Read all directions thoroughly. Always wear gloves and eye protection.

BASIC USE: SEAL-KRETE® Heavy Duty Waterproofer is a water-based, 25% solids, acrylic formula designed to stop water penetration into low density or porous vertical concrete and masonry surfaces such as split-face or fluted concrete block. SEAL-KRETE Heavy Duty Waterproofer provides a tough, flexible, breathable film which prepares these surfaces for painting. It's also excellent for binding chalky surfaces on painted or bare vertical substrates including concrete block, tilt-ups, stucco and aluminum siding. Unbeatable for strengthening mortar joints, SEAL-KRETE Heavy Duty Waterproofer lowers surface pH on alkaline substrates and revitalizes the natural colors of surfaces including aged vinyl siding, aluminum siding and stucco. Added to paint, SEAL-KRETE Heavy Duty Waterproofer improves spread rate, increases coverage and extends paint life.

SURFACE PREPARATION: All surfaces must be clean and dry. Remove any loose or peeling paint and excessive chalk. Repair all cracks and surface breaks. Cover windows, doors, etc., prior to application. Use caution when applying on windy days. Remove any overspray immediately with water.

APPLICATION: Do not apply if rain is expected within 12 hours. Temperatures should not fall below 50°F within 24 hours of application. Ready to use - do not dilute. Apply SEAL-KRETE Heavy Duty Waterproofer using a garden sprayer, airless sprayer, brush or roller. Spray applications should be backrolled to assure proper surface penetration. Apply a minimum of 2 flood coats, allowing a minimum of 2 hours dry time between coats. SEAL-KRETE Heavy Duty Waterproofer goes on milky white, which aids in complete surface application, but dries clear.

NEW STUCCO: Paint up to 3 weeks faster. Apply 2 coats of SEAL-KRETE Heavy Duty Waterproofer 10 days after stucco has been placed to effectively lower surface pH. Paint when dry.

COLORED STUCCO: SEAL-KRETE Heavy Duty Waterproofer can be applied to colored stucco during the curing process to reduce bleeding and discoloration.

COVERAGE: 50-300 sq.ft. per gallon. Coverage will vary based on surface porosity. Coverage of second coat application is 50% greater per gallon.

DRY TIME: SEAL-KRETE Heavy Duty Waterproofer typically dries in 2-4 hours, depending on temperature and humidity.

TOPCOATING: SEAL-KRETE Heavy Duty Waterproofer can be topcoated when dry, with latex, oil-based or elastomeric coatings.

TINTING: SEAL-KRETE Heavy Duty Waterproofer can be tinted up to 4 oz. per gallon using universal colorants.

LIMITATIONS: FOR VERTICAL SURFACES ONLY – DO NOT USE ON HORIZONTAL SURFACES including driveways, garage floors, wood decks and roof tiles. Do not use on swimming pools, bird baths or water features. Do not apply below grade or where hydrostatic pressure is likely to develop. Do not apply if rain is forecast within 8 hours of application. Keep from freezing.

TECHNICAL SUPPORT: For more information, technical assistance or to obtain a Material Safety Data Sheet, visit our website or call our technical service department M-F, 8am-5pm EST at 1-800-323-7357.

CAUTION: KEEP OUT OF REACH OF CHILDREN.

FIRST AID: For Eye Contact: Flush with water for 15 minutes. For Skin Contact: Prolonged contact may cause irritation. Wash affected area with soap and water. **If Swallowed:** Induce vomiting and seek immediate medical attention. **Inhalation:** If headache or nausea is experienced, remove the individual to fresh air. If symptoms persist, seek medical attention.



| PRODUCT NUMBER | UNIT SIZE | UPC CODE | CARTON QTY | CARTON CODE | CARTON SIZE (L X W X H) | CARTON SIZE (CUBIC FEET) | CARTON WT. (LBS) | PALLET QTY. (CARTONS) |
|----------------|-----------|-----------------|------------|--------------------|-------------------------|--------------------------|------------------|-----------------------|
| 700001 | 1 GALLON | 0 15944 70001 5 | 4 | 9 00 15944 70001 8 | 15 X 9.5 X 12.5 | 1.03 | 36 | 36 |
| 700005 | 5 GALLON | 0 15944 70005 3 | 1 | NA | 12 X 12 X 15 | 1.25 | 44 | 36 |



MAXIMUM PROTECTION • STOPS WATER PENETRATION



Apply Seal-Krete Heavy Duty with a garden sprayer, airless sprayer, brush or roller. Spray applications should be back-rolled to assure proper surface penetration.

LIQUID PROPERTIES

Solids: 25%
 Acrylic Resin: Proprietary
 Water Based
 Odor: Slight
 Appearance: Milky White - Dries Clear
 VOC: Less than 100 grams per liter

FOR USE ON VERTICAL SURFACES:

- Concrete
- Stucco
- Plaster
- EIFS
- Drywall
- Galvanized Metal
- Vinyl Siding
- Aluminum Siding
- Adobe
- Wood Fencing
- Masonite
- and more!

SEAL-KRETE HEAVY DUTY IS:

- Paintable
- Environmentally Safe
- Long-Lasting
- Tintable



Seal-Krete Heavy Duty is recommended for residential and commercial use on Split face block (above left) and fluted and decorative block (above right).

COVERAGE GUIDELINES

| Material | Coverage Approx. sq.ft./gal. |
|--------------------------|---------------------------------|
| Split-Face Block | 50 |
| Fluted Block | 50 |
| Concrete Block | 80 |
| Stucco | 150 |
| Concrete Slab / Tilt-ups | 175 |
| Wood Fencing | 175 |
| Aluminum Siding | 300 |
| Galvanized Metal | 300 |
| Adobe | 100 |
| Chalky Surfaces | 300 |

Actual coverage will vary depending on porosity of surface.
 For second coat application, increase coverage by 50%.

LIMITED 5-YEAR WARRANTY

A limited 5-year warranty is available on the quality and performance of this product on a per job basis. For full details on this warranty program, contact our technical service department. Otherwise, manufacturer/seller makes no warranty of any kind, except that this product is free from defect and is of merchantable quality. Buyer remedy for breach of warranty is limited to replacement of product or refund of purchase price.



Convenience Products
 306 Gandy Rd., Auburndale, FL 33823
 E-mail: tech@seal-krete.com or call
 1-800-323-7357
 Visit our web site at www.seal-krete.com