

# Quick Reference of Common Exterior Systems

Common Exterior Systems		1 <sup>st</sup> COAT	2 <sup>nd</sup> COAT	3 <sup>rd</sup> COAT	4 <sup>th</sup> COAT
JOINERY		CETOL HLS	CETOL FILTER 7 PLUS	CETOL FILTER 7 PLUS	<b>Recommended for exposed areas</b>
CLADDING	or	CETOL HLS CETOL HLS	CETOL HLS CETOL FILTER 7 PLUS	CETOL HLS CETOL FILTER 7 PLUS	
FASCIA & GABLES	or	CETOL HLS CETOL HLS	CETOL HLS CETOL FILTER 7 PLUS	CETOL HLS CETOL FILTER 7 PLUS	
LOUVRES		CETOL HLS	CETOL FILTER 7 PLUS	CETOL FILTER 7 PLUS	
FRONT DOORS GARAGE DOORS	or	CETOL HLS CETOL CLEARCOAT LB PLUS*	CETOL FILTER 7 PLUS CETOL CLEARCOAT HB PLUS*	CETOL FILTER 7 PLUS CETOL CLEARCOAT HB PLUS*	
SOFFITS		CETOL HLS CETOL CLEARCOAT LB PLUS*	CETOL FILTER 7 PLUS CETOL CLEARCOAT HB PLUS*	CETOL FILTER 7 PLUS CETOL CLEARCOAT HB PLUS*	
GATES	or	CETOL HLS CETOL HLS	CETOL HLS CETOL FILTER 7 PLUS	CETOL HLS CETOL FILTER 7 PLUS	
HANDRAILS	or or	CETOL HLS CETOL HLS CETOL HLS	CETOL HLS CETOL FILTER 7 PLUS CETOL NOVATECH	CETOL HLS CETOL FILTER 7 PLUS CETOL NOVATECH	CETOL HLS CETOL FILTER 7 PLUS
PERGOLAS	or or	CETOL HLS CETOL HLS CETOL HLS	CETOL HLS CETOL FILTER 7 PLUS CETOL NOVATECH	CETOL HLS CETOL FILTER 7 PLUS CETOL NOVATECH	CETOL HLS CETOL FILTER 7 PLUS
SPA/SAUNA/POOL AREAS	or	CETOL HLS CETOL HLS	CETOL HLS CETOL FILTER 7 PLUS	CETOL HLS CETOL FILTER 7 PLUS	-
SHINGLES		CETOL HLS	CETOL HLS	CETOL HLS	-
DECKING DOOR SILLS	or	CETOL HLS CETOL HLS	CETOL HLS CETOL DECK or DECK PLUS	CETOL HLS CETOL DECK or DECK PLUS	-
OUTDOOR FURNITURE	or	CETOL HLS CETOL NOVATECH	CETOL HLS CETOL NOVATECH	CETOL HLS -	-

\* Cetol Clearcoat should only be used on south and east facing protected aspects

The use of flat sawn timber (crown/arrowhead grain pattern) in high sunshine areas will significantly reduce the lifespan of your coating. Flat sawn, dressed weatherboards should be sanded with 80-100 grit sandpaper to slightly roughen surface and remove mill glaze. Flat sawn timber (particularly cedar) has a much higher tendency to distort than quarter sawn timber. Sorting of quarter sawn timber for use in high sunshine areas prior to fixing or manufacture is recommended by BRANZ in their publication "BRANZ Selecting Timber Guide (August 2004)". Coating lifespan can be significantly reduced when used in elevated, seaside or exposed north facing situations. Dark colours such as ebony will have a shorter maintenance cycle.