



Synteko Solid 1612 Flooring Oil

120.20
1/2 pages
March 2010

Description

Synteko Solid Oil is an alkyd based high solid oil. Oxygen curing and provides a beautiful smooth finish.

General Notes

Main characteristics:

- Excellent resistance to wear.
- Suitable for commercial use.
- Suitable for most types of timbers.
- Easy maintenance.

Use:

A clear finish oil for wooden and cork floors indoors. This oil can also be applied to parquet floors, doors, bars, furniture, kitchen bench tops.

Application Data

Conditions of application:

Application temperature: 15-25°C.

Method:

Shake thoroughly before use.
Pour directly onto floor and spread by:
Brush.
Paint roller.
Floor spreader.
Spatula.

Thinning:

N/A

Cleaning of equipment:

Mineral Turps.

Recommended film thickness:

N/A

Coverage rate per litre:

The coverage rate greatly depends on the method of application being used and the nature of the substrate to be coated.
Approximately 10 – 20m²

Drying times at 23°C / 50% relative humidity:

Approximately 16 hours.
Low temperatures and/or high humidity can delay drying times.

Practical Application Data

See application information by specific area. Refer to Index.

Properties

Viscosity:

130 cP ICI @ 23°C

Density:

Approximately 0.940 Kg/m³.

Solids content:

Dry solid 90%

Gloss level:

N/A



Synteko Solid 1612 Flooring Oil

120.20
2/2 pages
March 2010

Properties (continued)

Flow:	N/A
Adhesion:	N/A
Wear resistance:	The system has excellent resistance to wear.

Further Information

Container sizes:	1 & 5 litre cans.
Minimum shelf life:	25 months if stored in unopened packing.
Storage:	Store in a dry and cool place between +5 - -30°C
Colour range:	N/A

Health and Safety Aspects

Flash point	+76 °C.
HAZCHEM:	3YE.
Transport Code:	UN1263.
Labelling:	Health and safety information according to EEC directive: R21: Harmful in contact with skin R38: Irritating to skin. R40: Limited evidence of a carcinogenic effect R41: Risk of serious damage to eyes. R43: May cause sensitization by skin contact. R65: Harmful: may cause lung damage if swallowed. R66: Repeated exposure may cause skin dryness or cracking. S23: Do not breathe vapour and spray mist. S51: Use only in well ventilated areas. P58: Contains drying oils. Risk of self-ignition.

Government regulations: The user of this product is required to comply with the national statutory regulations for health and safety at work and waste disposal.

Ventilation requirements: Provide adequate ventilation. Where reasonably practical this should be achieved by the use of exhaust ventilation and good general extraction. If these are not sufficient to maintain concentrations of particulates and solvent vapours below the Occupational Exposure Limits, suitable respiratory protection must be worn.

Please Note

- Every care is taken to ensure that the information provided in this data sheet is accurate. Jac Jay Limited is unable to guarantee results as it has no control over the conditions under which products are applied, the substrate or the application. The customer has to determine the suitability of the delivered products or information for its intended purpose.