

Description

A fast drying interior or exterior filler/stopper for use on softwoods and hardwoods.

General Notes

Main characteristics:

- Quick Drying
- Easily abraded
- Excellent adhesion
- Excellent recoatability with woodstains, opaque or clear finishes

Use:

For small repairs such as nail holes and minor surface defects. Can be used with colourless or coloured woodstains. Suitable for use under opaque finishes.

Application Data

Conditions of application:

Do not apply if there is a risk of rain, or when air/substrate temperatures are below 5°C during application or drying periods. Protect from frost and rain until dry. Do not apply to timber surfaces with a moisture content above 18%.

Method:

Apply by clean filling knife working the product well into the substrate. Fill slightly 'proud'.

Cleaning of equipment:

Wash equipment with cellulose thinners immediately after use.

Recommended film thickness:

Apply up to a thickness of no more than 5mm per layer.

Practical Application Data

See application information by specific area. Refer to Index.

Properties

Composition:

Nitro-cellulose.

Setting Time:

Dry and recoatable after 2 hours and under normal drying conditions. Minimum recommended application temperature 50°C. At lower temperatures and/or conditions of high relative humidity, drying periods will be extended.

Solids content:

99%.

Adhesion:

Excellent adhesion.

Further Information

Container sizes:	150ml
Storage:	Keep in a cool, dry place.
Colour range:	Dark Oak, Light Oak, Mahogany, Meranti, Merbau, Natural and Teak. The above is a guide for the selection of the correct shade to match various timbers. Because of the variable nature of timber, an approximate guide can only be given and if in doubt a trial area should be carried out.

Health and Safety Aspects

Flash point (DIN 53213):	> 21°C.
Transport code:	UN 1263
Hazchem code:	3YE
Labelling:	Health and safety information according to EEC-Directive: R12: Highly Flammable. R20: Harmful by inhalation. S16: Keep away from sources of ignition - No smoking.
Government regulations:	The user of this product is required to comply with the national statutory regulations for health and safety at work and waste disposal.
Ventilation requirements:	Minimum required to comply with MAC*, LEL* or UEL*. LEL 10%

- * MAC = Maximum Acceptable Concentration.
MAC = TLV – Threshold Limit Value, as determined by the American Conference of Governmental Industrial Hygienists.
- * LEL = Lower Explosion Limit.
- * UEL = Upper Explosion Limit.
- * PPM = Parts Per Million.

Points to Note

- Prior to use, all surfaces should be suitably dry, clean and free from anything that will interfere with the adhesion of the materials to be applied, e.g. resins, extractives, organic growth, etc.
- Apply layers as necessary not exceeding 5mm at a time. Ensure each layer is dry before overcoating.

Please Note

- Every care is taken to ensure that the information provided in this data sheet is accurate. Jac Jay Limited is unable to guarantee results as it has no control over the conditions under which products are applied, the substrate or the application. The customer has to determine the suitability of the delivered products or information for its intended purpose.