



Product information

SYNTEKO SOAP 1617

GENERAL DESCRIPTION

Synteko Soap is suitable to be used after treatment of wooden floors with Synteko Solid 1612 and Synteko Belle 1614. The product can also be used for cleaning and maintenance of natural wood. It is also possible to use the product on surfaces treated with floor finishes and also on ceramic or natural stone floors.

TECHNICAL DATA

Base material	Yellow potash soap based on coconut/soy-oil derivatives and complex forming agents
Viscosity	Low viscous liquid
pH	Alkaline
Flash point	> +100°C
Shelf life	12 months in unopened container
Storage	Store frost-free. Must be stored between +5°C (+40°F) and +30°C (+86°F)

DIRECTIONS FOR USE

Hardwood floors treated with Synteko Solid 1612, Synteko Belle 1614.

When necessary, for regular cleaning, but not earlier than one week after oil treatment, floors may be washed with a 1 to 20 dilution of Synteko Soap in lukewarm water, using a well wrung cloth.

ENVIRONMENTAL DATA

Keep out of reach of children. Detailed information and guidance is provided in our MSDS (Material Safety Data Sheet).



Akzo Nobel Decorative Coatings AB
Synteko Floor Finishes
SE-205 17 Malmö, Sweden
Phone: +46 40 355000
www.synteko.com
Email: info@synteko.com



Our information is based on laboratory tests and is considered a guide in connection with choice of product and working method. As your working conditions are beyond our control, we do not assume any responsibility for the results. Our responsibility covers exclusively personal injury and damage to property, which actually have been proved subsequent to faults and defects in one of the products manufactured by us.

Date: 2002-10-30